Doc W 1 UN 408



ARMORED MEDICAL RESEARCH LABORATORY

FORT KNOX, KENTUCKY

INDEXED

Report On

PROJECT NO. T-12 - TEST OF EAR PROTECTIVE DEVICES - SILENTS

ARMY MEDICAL MAY 27 1946 LIBRARY

INFORMATION COPY

Action copies have been forwarded to Office of the surgeon General, Occupational Hygiene Branch for approval and execution.

Project No. T-12

15 October 1945

ZI.S. Armored medical research laboratory,
Fort knox, ky.

Project no. T-12

ARMORED MEDICAL RESEARCH LABORATORY Fort Knox, Kentucky

SPMEA 741-2 Project No. T-12 15 October 1945

- 1. PROJECT: No. T-12, Test of Ear Protective Devices Silents.
 - a. Authority: 1st Indorsement, ASF, SGO 17 July 1945, (SPMDO).
- b. <u>Purpose</u>: To test and evaluate subject ear protective device compared to the device now standardized by ASF for procurement and issue.

2. DISCUSSION:

- a. The requirement for acoustic protection for military personnel to prevent damage from gun fire and blast has been clearly shown in an earlier report. (AMRL, Project No. 26, dated 5 August 1944).
- b. Various types of ear protective devices are available, some more suitable for military use than others. Consideration in the selection of a device must be given to blast protection, comfort, attenuation of spoken voice, cleanliness, and sizing.
- c. A recommendation for adoption would necessarily require a competitive ear protective device to be superior in quality to the present standardized ear protective device, V5lR (Ear Wardens).
- d. The subject ear protective devices, Silents, were tested and comparisons were made with the NDRC, V51R (Ear Warden), using a group of 7 men as subjects.

3. CONCLUSIONS:

- a. Blast protection and attenuation offered by subject device were slightly inferior to standardized V51R ear protector.
- b. For periods of wear of one hour or longer the Silents were uncomfortable and irritating.
- c. Universal size arrangement of subject plug is a desirable feature of the subject device.
- d. The principle of closing the ear canal entrance rather than depending upon an insert into the canal is desirable, providing a satisfactory acoustic seal is maintained.

Propert So. Tell

25 Owners Link

PROJECT: Sc. T-12, Carb of Ast Protective Desires . St. sel

as Authorities has indorparent, ASP, SOO 19 AGE 1945, (SPICO),

Commented to the device not an anaderstand by the for propertunest and large.

Transamu

to The recutrement for absentic profession for allinery personner, the present density for the Sun Tire and Since has need clearly about to an evilous ropers, (Aut., Disject No. Ms. Material Autumnt. 1964).

sufficient for maintainty and possess of second construction of the solicition of a constitution of a

productive cortact field (for adjusted in tental to the present reductive and productive

to the suclect ast protection devices, Silents, were instanted for a support of a suclection.

A PROPERTY.

the Mann probabled and Attendance of the to address device and

DESCRIPTION OF RESPECTATION OF SHEET OF

or one surface decision.

The principle of the same of t

4. RECOMMENDATIONS:

a. That subject ear protective device, Silents, be considered less satisfactory than the ASF standardized issue ear protectors, V51R (Ear Warden).

Submitted by:

Robert H. Walpole, Captain, FA

3 Incls.

Incl. #1 - Appendix

Incl. #2 - Figure 1

Incl. #3 - Figure 2A - 2B

APPROVED William B. Bean WILLIAM B. BEAN

Major, Medical Corps

Commanding

a. That am year ast mutachive device, billents, be admitted to be conficuld to be conficuld to be admitted to b

Superior of the

Rebert M. Malpois, Captain, 75

3 living hel. \$1 - Appendix livel. \$2 - Figure 1

APPEDING COMMENDED TO ASSESSED.

ANALOT, MALLEN COMM.

Commenting

1. DISCUSSION:

The requirements of acoustic protection for military personnel exposed to blast and gun fire were presented in an earlier report (AMRL, Project 26, dated 5 August 1944). Subsequent to that date Army Service Forces standardized and procured for issue an ear protective device, V51R (Ear Warden), developed by the National Defense Research Council, which is equal or superior to available commercial type protective devices. Obviously any device proposed to replace the standardized plug must prove superior.

Consideration in the selection of a suitable ear protective device must be given to blast protection, comfort, attenuation, cleanliness, and sizing. To achieve maximum blast protection an adequate acoustic seal must be maintained which may be accomplished by inserting a plug into the outer ear canal, or covering the entrance to the canal. Of importance in maintaining the seal is a satisfactory design of the protective device to insure its remaining in proper position without frequent adjustment by the wearer. For a plug to be worn in preference to cotton or other less satisfactory acoustic material, it must be comfortable, and must not produce irritation or chafing. Attenuation, a measure of the ability to hear voice conversation with the device inserted, is important from the viewpoint of receiving commands. Sizing of plugs, of course, is a real consideration, one which will allow a maximum number of adequate fits for a maximum number of men with a minimum quantity of plugs. For this a universal adjustable fit is desirable. Present standardized protective device is issued in three sizes, designed to fit a maximum number of ears.

2. DESCRIPTION OF EAR PROTECTIVE DEVICE, SILENTS:

This device is a molded, synthetic rubber, two-piece ear plug. (See Figure 1). A conical shaped piece attached to a stem is inserted in the entrance of the ear canal. A second piece, shaped much like a wing nut is inserted below the anthelix to keep the plug in place. This section is adjustable to allow for varied ear sizes by sliding on the stem. Once adjusted the friction between the two rubber parts maintains this adjustment.

3. DESCRIPTION OF TEST:

Of a group of 25 men whose ears were medically examined, 15 were selected who had no apparent disability. Of these 15, seven, ages 19 to 27 years, who had the best hearing, based on repeated audiograms performance using a Maico Audiometer in a quiet room, were selected for test.

In order to make a comparison with the V51R protector, tested several months previously, the same test procedure was followed with the Silents. Each subject with the device in one ear was exposed to the blast from three consecutive rounds of 75 mm cannon, his test ear normal to the muzzle at a distance of six feet. Immediately following this exposure an audiogram was again made. The audiogram difference in values for each frequency represented the loss suffered

A. DESCRIPTION

to other and sum fire more presented to an entitled repert (1981, Project 20, Marian I and an interest of the Services administration and procured for decide an entitle for the Variable for decide an entitle for the Variable for the protective decided, which is equal or superior to realisate community decided to the forest of the decided by the protective decides, the decide or superior to replace the missing the forest or superior to the forest or superio

designations in the established as proceeding and the established as proceeding and include and included as an included as a secondariated by the established as a secondariated as a se

DESCRIPTION OF THE PROTECTIVE DETUGE, STANKS.

The ser rained in a motival place effection to a tree to inserbed to the course of the

IN THE PERSON NAMED IN COLUMN

The particular of a distance of the particular design of the particular

AND THE PROPERTY OF THE PROPER

due to the blast exposure. The other ear tightly covered by the subject's hand and away from exposure, was also checked by an audiogram to serve as an unexposed control.

The average less for each of 10 given pure tone frequencies was then determined for the 7 subjects and the values plotted on a curve. For comparison with the V51R protective devices tested earlier, the values obtained at that time for twelve subjects were also plotted on this curve. (See Figure 2A).

To obtain information on the relative attenuation of the two devices, results of tests on these 7 subjects wearing the Silents were compared to those of the 12 subjects who earlier wore the V51R devices. (See Figure 2B).

At the end of the tests the men were questioned regarding comfort of wear and ability of the device to remain in place.

4. RESULTS OF TEST:

Hearing loss following blast exposure was slightly greater with the subject plug than with the V51R device. Maximum loss difference was 2Db, which is within an allowable error as affected by exterior noise level. (See Figure 2A).

Attenuation tests, illustrated in Figure 2B, for the two devices show the V51R to be superior to Silents for the center speech range as well as for the ten pure tones from 128 to 11584 C.P.S.

Five of the 7 subjects complained that the Silents were uncomfortable to wear after one hour, the remaining two experienced no discomfort. These 5 men stated that they would prefer wearing cotton or waste in spite of the reduced insulation offered. None of the subjects experienced pain or shock from the blast exposure.

5. CONCLUSIONS:

The Silents ear protective device offers considerable advantages over many commercial ear protectors, but fails to show an advantage over the ASF standardized ear protector, V51R (Ear Warden). The universal size arrangement of this device is a desirable feature as is the principle of an acoustic seal covering the entrance of the ear canal. The discomfort and irritation experienced by wearers is a disadvantage, probably due to the stiffness of the rubber material.

need only dead to the exponents, was need theread by an audiogram to never in an analysis of the following

The average lass for each of M. given pure tong-fragmancies was then centermined for the Fauly and the values and the values plotted on a certain for owner. Lean with the VIII protective devices therefor earlier, the values obtained at their bins for their major subjects were also plotted on this curve. [des figure and].

To obtain information on the relative attenuation of the two devices, required of the two devices, in Thosa of the tablects who serials were the Villa devices. (See Figure 28).

At the end of the seats the sen ears questioned regarding confort of wew and shilling of the device to retain in place.

HE THE OR LEGIS

Meaning loans following block expensive was aligned greater at the subject plug them with the Vill device. Meading loss difference are 210, or on its aligned as allowable error as affected by exterior coise level. (See Figure 21)

Attendation beats, themselved in Figure 28, for the two dyname atom the TSAR to be expected to Milestic for the senter special range as real as follows wan pure tones from MMS to Light 6,7.5.

Tive of the "subjects traplated that the Silents wars uncertaints to an early effect one now, the parameter is expectationed to despendent, then I have attacked that they muid penden wasting mesting mesting account wasts in applie of the Year deed format from the transfer of the subjects experienced pure of each too the bank appearance.

S. CHRISTING

The Director men protection of the latter on store an executary over the all managements of the protection of the anti-control of the anti-control

Project T-12

"Silent" Ear Protector

ARMORED MEDICAL RESEARCH LABORATORY
FORT KNOX, KY.

Figure 1

Incl. 42



FIG. 2A

TEMPORARY LOSS ABOVE NORMAL FOLLOWING STANDARDIZED EXPOSURE





FIG. 2B AVERAGE ATTENUATION OF TEST EAR DEVICES NDRC VSIR X HEARING LOSS, Db SILENTS XX FREQUENCY, C.P.S.



FOLLOWING STANDARDIZED EXPOSURE

FIB. SA